Amendments to the Claims:

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A single channel method for estimating a halftone screen frequency from image data, comprising:

multiplying a frequency measurement signal by a factor;

adding the multiplied frequency measurement signal to an image data signal to produce an output signal;

adjusting the factor multiplied to the frequency measurement signal based on a control signal, wherein the control signal is based on a characteristic of the image data; ~~and~~

interpolating the output signal to produce the halftone screen frequency ~~estimate.~~estimate; and

subtracting a frequency signal from the image data signal, to produce the frequency measurement signal.

2. (Original) The method of claim 1, further comprising:

measuring a contrast within a window of the image data to produce the control signal.

3. (Original) The method of claim 1, further comprising:

filtering the image data using a low-pass filter to produce the image data signal.

4. (Original) The method of claim 1, further comprising:

sub-sampling the image data to produce the image data signal.

5-6. (Canceled)

7. (Previously Presented) The method of claim 1, further comprising:

outputting the output signal which is an estimate of the halftone screen frequency, to a de-screening device.

8. (Currently Amended) An apparatus for estimating a halftone screen frequency, comprising:

a multiplier which multiplies a frequency measurement signal by a factor;

a combiner which combines the multiplied frequency measurement signal with an image data signal to produce an output signal;

an adjuster which adjusts the factor multiplied to the frequency measurement signal based on a control signal, wherein the control signal is based on a characteristic of the image data; and

an interpolator for interpolating the output signal to produce the halftone screen frequency ~~estimate.~~estimate; and

a subtracting module for subtracting a frequency measurement from the image data signal, to produce the frequency measurement signal.

9. (Original) The apparatus of claim 8, further comprising:

a contrast measuring device which measures contrast within a window of the image data to produce the control signal.

10. (Original) The apparatus of claim 8, further comprising:

a low-pass filter for filtering the image data to produce the image data signal.

11. (Original) The apparatus of claim 8, further comprising:

a sub-sampling filter for sub-sampling the image data to produce the image data signal.

12-13. (Canceled)

14. (Previously Presented) The apparatus of claim 8, further comprising:

an output device for outputting to a de-screening device the output signal which is an estimate of the halftone screen frequency.

15. (Currently Amended) A single channel apparatus for estimating a halftone screen frequency, comprising:

means for measuring a contrast of image data;

means for adjusting a factor multiplied to a frequency measurement signal based on the measured contrast;

means for combining ~~a~~ the multiplied frequency measurement signal with an image data signal to produce an output signal;

~~means for adjusting a factor multiplied to the frequency measurement signal; and~~

means for interpolating the halftone screen ~~frequency.~~frequency; and

means for subtracting a frequency measurement from the image data signal, to produce the frequency measurement signal.

16. (Canceled)

17. (Previously Presented) A tangible computer-readable medium that stores computer-executable instruction which, when executed by a computer, causes the computer to perform the method of claim 1.

18-19. (Canceled)